




LINEAR MOTOR LMU040



This model is suitable for applications where high amount of force, high speed, and quick acceleration are required for operation, such as large scale production equipment and precision positioning equipment.

Standard Specifications


Insulation Capacity	: AC1500V 1min
Operating Range	: 0~25°C
Cooling Method	: Self-cool
Insulation Resistance	: DC500V 100MΩ or more
Operating range (in controlled environment)	: 20~80%(No condensation)
Maximum temperature	: 125°C

Specification

Parameter	Unit	LMU040-CP144		LMU040-CP204		LMU040-CP264		LMU040-CP384		LMU040-CP504	
		A	B	A	B	A	B	A	B	A	B
Performance Specifications											
Continuous Force	N	200		250		335		440		600	
Peak Force	N	1400		1750		2345		3080		4200	
Electrical Specifications											
BEMF Constant(line-line,peak)	V/(m/s)	75.45	37.72	113.18	56.60	150.90	75.45	128.05	64.02	170.72	85.37
Continuous Current	Arms	2.16	4.31	1.80	3.59	1.80	3.61	2.79	5.59	2.86	5.71
Peak Current,Stall	Arms	15.09	30.17	12.57	25.14	12.63	25.27	19.56	39.11	20.00	40.00
Force Constant	N/Arms	92.8	46.4	139.21	69.62	185.61	92.8	157.5	78.75	209.99	105
Motor Constant	N/√W	21.47		24.01		27.76		28.34		32.57	
Resistance,25°C (line-line)	Ω	14.6	3.54	21.24	5.31	28.32	7.08	12.72	3.2	16.96	4.24
Inductance,(line-line)	mH	9.6	2.4	15.2	3.8	18.4	4.6	7.2	1.8	10.8	2.7
Thermal Resistance	°C/W	0.89		0.78		0.58		0.42		0.3	
Maximum Bus Voltage	V _{DC}	340		340		340		340		340	
Mechanical Specifications											
Coil Weight	kg	1.1		1.6		2.1		3.1		4.2	
Coil Length	mm	144		204		264		384		504	
Magnet Track Weight	kg/m	21.8									
Magnetic Pole Pitch (NN)	mm	60									

- Notes :
- 1.Performance is dependent upon heat sink configuration, system cooling conditions,and ambient temperature.
 - 2.Values shown @ 100°C rise above a 25°C ambient temperature,with motor mounted to the specified aluminum heat sink.
 - 3.Peak force assumes correct rms current;consult SMJ.
 - 4.Force constant and motor constant specified at stall.
 - 5.All performance and electrical specifications±10%.

Dimensions(mm)



Magnet Plate			
Model No.	A	B	C
LMU040-MP240	240	4	2
LMU040-MP300	300	5	4

Coil Plate			
Model No.	D	E	F
LMU040-CP144	144	8	4
LMU040-CP204	204	12	4
LMU040-CP264	264	14	8
LMU040-CP384	384	22	12
LMU040-CP504	504	30	16